
Appendix A:

Skateable Bench at Vic West Park: Drawing Package


| CHLID | | | | | | | | KEY MAP NOT TO SCALE | | |
|--------------|----------------------|-----------|--|------|-----------|-------------|--|---|-----|---|
| | | | | | | | | DYLAN TOBY MEMORIAL BENC VICTORIA WEST SKATEPARK City of Victoria, B.C. | H a | Date gkc/sp Oct 8, 2020 Shecked Project # Approved Scale Designed gkc |
| – Dwg. No | - REFERENCE DRAWINGS | – DATE | | DATE | REVISIONS | BY APPROVED | | Services Ltd. 207-2276 C | | |







۲



SCALE 1:20


-


2.40m

2.15m

TOP VIEW SCALE 1:20


0.150m





SECTION A

GALVANIZED GRIND EDGE HSS WITH REINFORCEMENT.



SECTION B



ISOMETRIC VIEW

- 1. ALL CONSTRUCTION AND MATERIALS TO BE IN ACCORDANCE WITH THE CITY OF VICTORIA, MMCD PLATINUM EDITION 2009, AND THE BC BUILDING CODE.
- 2. ALL DIMENSIONS ARE IN mm AND ALL ELEVATIONS ARE IN m UNLESS NOTED OTHERWISE.
- 3. CONTRACTOR TO CONFIRM LOCATION OF AND COORDINATE WITH APPLICABLE UTILITIES PRIOR TO INSTALLATION OF ANY OF THESE WORKS.
- 4. NO DESIGN CHANGES ARE PERMITTED UNLESS THERE IS PRE-WRITTEN APPROVAL FROM THE ENGINEER.
- 5. MATERIAL SUBSTITUTIONS ARE ACCEPTED ONLY BY WRITTEN PRE-APPROVAL OF THE ENGINEER AND THE CITY OF VICTORIA. FOR ANY AMBIGUITIES IN SPECIFICATIONS THE MOST CONSERVATIVE/ROBUST SPECIFICATIONS SHALL GOVERN.

6. ALLOW 48 HOURS FOR ENGINEER TO PERFORM CHECKS AND MAKE ANY ADJUSTMENTS PRIOR TO ANY CONCRETE POUR.

CONCRETE AND REINFORCING STEEL NOTES

9. ALL MATERIALS USED IN FABRICATION SHALL BE NEW, NOT PREVIOUSLY USED IN ANY APPLICATION.

- CONCRETE SHALL BE NORMAL WEIGHT, 5-7% AIR ENTRAINED WITH A MAXMUM 50-100mm SLUMP AND 20mm AGGREGATE SIZE, AND HAVE A MINIMUM 28-DAY COMPRESSIVE STRENGTH OF 32MPa.

10. ALL STEEL PRODUCTS SHALL BE C.S.A. G40.21M, STRUCTURAL STEEL 350W.

- 2. REINFORCEMENT SHALL BE COLD BENT WHENEVER BENDING IS REQUIRED.
- 3. PLACE CONCRETE IN A UNIFORM MANNER TO PREVENT THE FORMATION OF COLD JOINTS AND OTHER PLANE OF WEAKNESS. VIBRATE THE CONCRETE TO FULLY EMBED REINFORCING BARS.
- 4. DO NOT PLACE CONCRETE IN WATER, ICE, OR FROZEN GROUND.
- S FOR COL-MENTER AND IN-THE INVESTIGATION TO APPLICABLE C.S.A. CODES AND RECOMMENDATIONS. IN ETHER OSE, MATERIAS CONTAINING CHEDRIE, CUCIUM, SUITS, ETC SHILL NOT BE USED. PROTECT FRESH CONCRETE FROM WRATHER FOR 7 DAY MINIMUM.
- 6. THESE DRAWINGS DO NOT SHOW THE COMPONENTS THAT MAY BE NECESSARY FOR CONSTRUCTION SAFETY. THE CONTRACTOR IS RESPONSIBLE FOR SAFETY IN AND ABOUT THE JOB STEE DURING CONSTRUCTION, AND THE DESIGN AND ERECTION OF ALL TEMPORARY STRUCTURES, FRAMEWORK, FALSENGRY, SHORING, CET CONJUNCTE THE WORK.

THE CONTRACTOR IS TO CALL B.C. ONE CALL, AND HAVE EXISTING U/G SERVICES STAKED PRIOR TO ANY CONSTRUCTION

ВC 4 CALL 1-800-474-6886 CELLULAR *6886

MI SON ST.

VICTORIA WEST

SKATE

STE

ESQUIMALT RD.

HENRY ST. à

0

PRELIMINARY Not for Constructio

- AS IS USUALLY THE CASE OF NEW CONSTRUCTION, ASSUMPTIONS HAVE BEEN MADE CONCERNING THE DESIGN. WE THEREFORE, EXPECT CHANGES THROUGHOUT THE CONSTRUCTION PROCESS. ALL OF THE STRUCTURAL INFORMATION ON THIS DRAWING IS SUBJECT TO REVISION.
- 8. DO NOT POUR CONCRETE UNTIL THE ENGINEER'S REVIEW IS COMPLETE. PROVIDE AT LEAST 48 HOURS ADVANCE NOTIFICATION WHEN SITE REVIEWS ARE REQUIRED.