#### NO. 16-080

## SANITARY SEWER AND STORMWATER UTILITIES BYLAW, AMENDMENT BYLAW (NO. 4)

#### A BYLAW OF THE CITY OF VICTORIA

The purpose of this Bylaw is to increase the stormwater user fee factor rates, CRD sewer consumption charge payable, connection fees, dye tests fees, and special fees and considerations payable under the *Sanitary Sewer and Stormwater Utilities Bylaw 14-071*.

#### Contents

- 1 Title
- 2 Section 27A
- 3 Schedule "A"
- 4 Effective date

Under its statutory powers, including section 194 of the *Community Charter*, the Council of the City of Victoria enacts the following provisions:

#### Title

1 This Bylaw may be cited as the "SANITARY SEWER AND STORMWATER UTILITIES BYLAW, AMENDMENT BYLAW NO. 4)".

#### Section 27A

2 Section 27A to the Sanitary Sewer and Stormwater Utilities Bylaw 14-071 is amended by repealing the existing Section 27A and replacing it with the updated Section 27A to this bylaw amendment.

#### Schedule "A"

3 Schedule "A" to the Sanitary Sewer and Stormwater Utilities Bylaw 14-071 is amended by repealing the existing Schedule "A" and replacing it with the updated Schedule "A" to this bylaw amendment.

#### Effective date

4 This Bylaw comes into force on January 1, 2017.

| READ A FIRST TIME the  | day of | 2016 |
|------------------------|--------|------|
| READ A SECOND TIME the | day of | 2016 |
| READ A THIRD TIME the  | day of | 2016 |
| ADOPTED on the         | day of | 2016 |

CITY CLERK MAYOR

## 27A. CRD Sewer Consumption Charge

(1) Pursuant to the powers of the City under the Additional Powers Regulation, B.C. Reg. 236/2002, a rate of \$2.72 for the months of June through September and a rate of \$3.88 for all other months multiplied by the number of units of water used at the owner's premises must be paid by each owner in respect of a portion of the annual operating costs and debt costs of the Capital Regional District Liquid Waste Management Core Area and Western Communities Service that are payable by the City.

#### **SCHEDULE "A"**

#### **FEES AND CHARGES**

## 1. Sanitary Sewer Use Charge

The sanitary sewer use charge for each unit of water used for the months of June through September is \$1.52 and for all other months is \$2.17.

## 2. Sanitary Sewer Service and Stormwater Service Connection Fees

| 1 – 100 mm                            | \$8800  |
|---------------------------------------|---------|
| 2 – 100 mm (in same trench)           | \$11800 |
| 1 – 150 mm                            | at cost |
| 2 – 150 mm (in same trench)           | at cost |
| 1 – 200 mm                            | at cost |
| 1 – 150 / 1 - 200 mm (in same trench) | at cost |
| 1 – 150 / 1 – 100 mm (in same trench) | at cost |
| 1 – 250 mm                            | at cost |
| 2 – 200 mm                            | at cost |
|                                       |         |

#### 3. Hub Connection Fees

\$1000 / hub connection

## 4. Dye Tests

\$200 for one visit to a single location or site, to a maximum of one hour

#### 5. Sewer Service Connection Test for Reuse or Abandonment

| 4 service connections or fewer     | \$250/visit/site |
|------------------------------------|------------------|
| Each additional service connection | \$100/visit/site |

#### 6. Sewer Service Connection Rehabilitation

| 1 – 100 mm | \$ 3500 |
|------------|---------|
| 1 – 150 mm | \$ 4000 |

## 7. Sealing a Discontinued Sewer Service Connection

\$1000 per service

#### 8. Special Fees and Considerations

All connection fees are for an application for a service connection to a single property unless otherwise stated. Service connection configurations not covered in this Schedule are subject to the Director's approval, and will be charged for "at cost".

Service connection fees under section 3 of this Schedule A include rock removal up to a depth of 1.0 m. All additional rock removal costs shall be paid by the applicant at cost.

At cost service connections must pay for all rock removal on an at cost basis. The estimated cost of rock removal shall be determined at the time rock is encountered.

These costs must be paid by the applicant prior to the City continuing the installation.

All service connections larger than 100 mm, and all connections installed on Arterial Roads or within the Downtown Core: at cost

All service connections that are requested to be installed outside normal working hours, where approved by the Director will be billed for at cost.

If the applicant is performing their own restoration on their property frontage in the area of a new service installation, at their cost, the Director will allow a rebate of \$200 per service trench.

#### 9. Contaminated Soil

Where the removal of contaminated soil is required it shall be done at cost.

#### 10. Archaeological Site

Costs associated with working in vicinity of an archaeological site shall be done at cost.

#### 11. Administrative Charges

Where work is performed at cost an administrative charge of 18% must be calculated and added to the "at cost" total.

#### 12. Stormwater User Fees

The stormwater user fee payable by an owner shall be determined by applying and totalling the four factors in the Stormwater User Fee Calculation Table below.

## Stormwater User Fee Calculation Table

| STORMWATER USER FEE CALCULAT   | TON TABLE                                |
|--|--|
| 1.A IMPERVIOUS SURFACES FACTOR   |  |
|  |  |
| _  | Fee (per sq meter)                       |
|  | \$0.6042                                 |
|  |  |
|  |  |
| 2.A STREET/SIDEWALK CLEANING FACTOR  |  |
|  |  |
|  | Fee (per meter)                          |
| Local  | \$1.67                                   |
| Collector  | \$3.76                                   |
| Arterial   | \$4.09                                   |
| Downtown   | \$40.25                                  |
| Downtown [   | Ψ-0.23                                   |
|  |  |
| 2.B INTENSITY CODE FACTOR  |  |
| Z.B INTENSITI CODE LACTOR  |  |
|  |  |
|  |  |
| Law Banaita Baaidantia I   | Fee (per property)                       |
| Low Density Residential  | \$0.00                                   |
| Multi Family Residential   | \$0.00<br>\$85.29                        |
| Multi Family Residential Civic/Institutional   | \$0.00<br>\$85.29<br>\$87.58             |
| Multi Family Residential   | \$0.00<br>\$85.29                        |
| Multi Family Residential Civic/Institutional   | \$0.00<br>\$85.29<br>\$87.58             |
| Multi Family Residential Civic/Institutional Commercial/Industrial                               | \$0.00<br>\$85.29<br>\$87.58             |
| Multi Family Residential Civic/Institutional   | \$0.00<br>\$85.29<br>\$87.58             |
| Multi Family Residential Civic/Institutional Commercial/Industrial                               | \$0.00<br>\$85.29<br>\$87.58<br>\$143.36 |
| Multi Family Residential Civic/Institutional Commercial/Industrial  2.C CODES OF PRACTICE FACTOR | \$0.00<br>\$85.29<br>\$87.58             |
| Multi Family Residential Civic/Institutional Commercial/Industrial                               | \$0.00<br>\$85.29<br>\$87.58<br>\$143.36 |

## 11. Rainwater Management Credit Program

## (a) Educational Programs

Except for a property that is used as a school, in order to qualify for a rainwater management credit an educational program for a Civic/Institutional or Commercial/Industrial property must relate to, describe and inform either the owner's employees or members of the public about a stormwater management facility that has been approved under the Rainwater Management Credit Program, that is located on the property, and that is functional and in good working condition. A qualifying educational program may include or consist of signs, brochures, or other graphic or printed information that is located in a prominent location on the property.

For a property that is used as a school, in order to qualify for a rainwater management credit an educational program must be included in the regular curriculum and form part of the regular teaching program for the school.

#### (b) Calculation of Credits

Where the owner of premises applies for participation in the rainwater management credit program, and the application is approved by the Director, a percentage credit for each approved credit type will be applied to the stormwater user fee in the amount(s) set out in the following tables.

## Rainwater Management Credit Table - Low Density Residential Properties

| Rainwater Best<br>Management Practice<br>(BMP)   | Minimum<br>Size   | Min. Roof Area<br>(m²) directed to<br>BMP | Ongoing<br>Credit |
|--|-------------------|---|-------------------|
| Cistern  | 1200L             | 25  | 10%               |
| Infiltration Chamber                             |                   | 25  | 10%               |
| Rain Garden                                      |                   | 25  | 10%               |
| Bioswale   |                   | 25  | 10%               |
| Permeable paving - no infiltration trench/piping | 10 m <sup>2</sup> |   | 10%               |
| Permeable paving - infiltration trench/piping    |                   | 25  | 10%               |

# Rainwater Management Credit Table – Multi-Family Residential, Civic/Institutional and Commercial/Industrial Properties

|                                      | Minimum<br>Impervious Area<br>Treated (%)  | Credit (%)  |
|--------------------------------------|--|---|
|                                      | 10   | 4   |
|                                      | 15   | 7   |
|                                      | 20   | 9   |
|                                      | 25   | 11  |
|                                      | 30   | 13  |
|                                      | 35   | 16  |
| Infiltration Chamber / Rain Garden / | 40   | 18  |
| Bioswale/ Permeable Pavement /       | 45   | 20  |
| Cisterns Plumbed for Indoors /       | 50   | 22  |
| Intensive Green Roofs                | 55   | 24  |
|                                      | 60   | 27  |
|                                      | 65   | 29  |
|                                      | 70   | 31  |
|                                      | 75   | 33  |
|                                      | 80   | 36  |
|                                      | 85   | 38  |
|                                      | 90<br><b>Minimum</b>   | 40  |
|                                      |  |   |
|                                      |  |   |
|                                      | Impervious Area  | Credit (%)  |
|                                      | Impervious Area<br>Treated (%)   | Credit (%)  |
|                                      | Impervious Area  | 2   |
|                                      | Impervious Area<br>Treated (%)<br>10   |   |
|                                      | Impervious Area<br>Treated (%)<br>10<br>15   | 2 3   |
|                                      | Impervious Area<br>Treated (%)<br>10<br>15<br>20                                   | 2<br>3<br>4   |
|                                      | Impervious Area<br>Treated (%)<br>10<br>15<br>20<br>25                             | 2<br>3<br>4<br>6  |
|                                      | Impervious Area<br>Treated (%)  10  15  20  25  30                                 | 2<br>3<br>4<br>6<br>7   |
|                                      | Impervious Area<br>Treated (%)  10 15 20 25 30 35                                  | 2<br>3<br>4<br>6<br>7<br>8  |
| Cisterns- Hand Use                   | Impervious Area<br>Treated (%)  10  15  20  25  30  35  40                         | 2<br>3<br>4<br>6<br>7<br>8<br>9   |
| Cisterns- Hand Use                   | Impervious Area<br>Treated (%)  10  15  20  25  30  35  40  45                     | 2<br>3<br>4<br>6<br>7<br>8<br>9   |
| Cisterns- Hand Use                   | Impervious Area<br>Treated (%)  10 15 20 25 30 35 40 45 50                         | 2<br>3<br>4<br>6<br>7<br>8<br>9<br>10                                     |
| Cisterns- Hand Use                   | Impervious Area<br>Treated (%)  10  15  20  25  30  35  40  45  50  55             | 2<br>3<br>4<br>6<br>7<br>8<br>9<br>10<br>11                               |
| Cisterns- Hand Use                   | Impervious Area<br>Treated (%)  10 15 20 25 30 35 40 45 50 55                      | 2<br>3<br>4<br>6<br>7<br>8<br>9<br>10<br>11<br>12                         |
| Cisterns- Hand Use                   | Impervious Area<br>Treated (%)  10 15 20 25 30 35 40 45 50 55 60 65                | 2<br>3<br>4<br>6<br>7<br>8<br>9<br>10<br>11<br>12<br>13                   |
| Cisterns- Hand Use                   | Impervious Area<br>Treated (%)  10  15  20  25  30  35  40  45  50  55  60  65  70 | 2<br>3<br>4<br>6<br>7<br>8<br>9<br>10<br>11<br>12<br>13<br>14             |
| Cisterns- Hand Use                   | Impervious Area Treated (%)  10 15 20 25 30 35 40 45 50 55 60 65 70                | 2<br>3<br>4<br>6<br>7<br>8<br>9<br>10<br>11<br>12<br>13<br>14<br>16<br>17 |

| Minimum         |            |
|-----------------|------------|
| Impervious Area | Credit (%) |

|  | Treated (%) |    |
|--|-------------|----|
|  | 10          | 3  |
|  | 15          | 5  |
|  | 20          | 7  |
|  | 25          | 8  |
|  | 30          | 10 |
|  | 35          | 12 |
|  | 40          | 13 |
| Cisterns - Irrigation System/ Extensive Green Roof | 45          | 15 |
|  | 50          | 17 |
| Green Rooi   | 55          | 18 |
|  | 60          | 20 |
|  | 65          | 22 |
|  | 70          | 23 |
|  | 75          | 25 |
|  | 80          | 27 |
|  | 85          | 28 |
|  | 90          | 30 |

## (c) BMP (Design and Construction Requirements) Table

The following table sets out additional requirements for the design and construction of stormwater retention and water quality facilities.

|                            | Tier A    |                  | Tier B, C & D    |
|----------------------------|-----------|------------------|------------------|
| ВМР                        | DIY Build | Contractor Build | Contractor Build |
| Rain Barrel                | 1         | 1                | N/A              |
| Cisterns - at grade        | 1         | 1                | 2                |
| Cisterns - below grade     | 3         | 3                | 3                |
| Cisterns - above grade     | 3         | 3                | 3                |
| Rain Gardens               | 1         | 1                | 2                |
| Bio Swales                 | 1         | 1                | 2                |
| Green Roof                 | N/A       | 3                | 3                |
| Permeable Paving without   |           |                  |                  |
| Infiltration Trench/piping | 1         | 1                | 2                |
| Permeable Paving with      |           |                  |                  |
| Infiltration Trench/piping | 2         | 1                | 3                |
| Infiltration Chamber       | 3         | 3                | 3                |

- 1 Design and construction must follow City standards and specifications.
- 2 Design and construction must follow City standards and specifications. Must be designed and installed under the supervision of a Qualified Designer.
- 3 Design and construction must follow City standards and specifications.

  Must be designed and installed under the supervision of a Qualified Professional.

  Green Roofs must be designed by and installed under the supervision of a Qualified Professional who is a professional architect or structural engineer

Inspections as required at specified intervals.

DIY Build - Owner is responsible for construction methods and adhering to design.

Failure to do so may result in rejection at owner's expense. City assumes no responsibility for rejection or liability for damages.

#### In the table above:

- (a) "Tier A", "Tier B", "Tier C" and "Tier D" mean, respectively, properties that are classified under section 28(4) of this bylaw as Low Density Residential, Multi-Family Residential, Civic/Industrial and Commercial/Industrial.
- (b) "DIY Build" means that the owner of Low Density Residential property constructs or installs the stormwater retention and water quality facility themselves, without the assistance of a contractor.